

Luminária Spot Downlight LED

JING
ILUMINAÇÃO



Indicado para uso:



ESCRITÓRIO



COMERCIAL



RESIDENCIAL

Características gerais:



25.000H
VIDA ÚTIL



BIVOLT



38°
FACHO



IRC



LED

CÓDIGO	POTÊNCIA	FLUXO LUM.	TEMP. DE COR	FP	DIMENSÃO	CÓDIGO EAN
55 132	15W	1120lm	3000K	>0,5	70x45mm	7898645635243
55 131	15W	1120lm	6500K	>0,5	70x45mm	7898645635236
55 134	20W	1500lm	3000K	>0,5	90x45mm	7898645635267
55 133	20W	1500lm	6500K	>0,5	90x45mm	7898645635250
55 136	30W	2250lm	3000K	>0,5	220x45mm	7898645635281
55 135	30W	2250lm	6500K	>0,5	220x45mm	7898645635274
55 138	40W	3000lm	3000K	>0,5	195x55mm	7898645635304
55 137	40W	3000lm	6500K	>0,5	195x55mm	7898645635298
55 140	50W	3750lm	3000K	>0,5	220x45mm	7898645635328
55 139	50W	3750lm	6500K	>0,5	220x45mm	7898645635311